



CA 250

PRIME
SERIES BY CALIBER




- Max power output at 14.4V:
2x 125W/4Ω
or **1x 400W/4Ω** (bridged)
- RMS output at 14.4V:
2x 50W/4Ω
or **1x 160W/4Ω** (bridged)
- RCA line input
- RCA line output
- High level input
- Bass Boost (0-6-12dB • 45Hz)
- Variable input sensitivity
- Overload and thermal protection
- Dimensions: 240(W) x 220(D) x 46(H) mm



- Puissance maximale à 14.4V:
2x 125W/4Ω
ou **1x 400W/4Ω** (ponté)
- RMS à 14.4V:
2x 50W/4Ω
ou **1x 160W/4Ω** (ponté)
- Entrée RCA
- Sortie RCA
- Entrée haut niveau
- Bass Boost (0-6-12dB • 45Hz)
- Sensibilité d'entrée variable
- Protection court-circuit et thermique
- Dimensions: 240(l) x 220(P) x 46(H) mm

Dimensions:





CA 250

PRIME
SERIES BY CALIBER



- Maximale Leistung bei 14,4V:
2x 125W/4Ω
oder **1x 400W/4Ω** (gebrückt)
- RMS-Ausgang bei 14,4V:
2x 50W/4Ω
oder **1x 160W/4Ω** (gebrückt)
- RCA-Linieneingang
- RCA-Leitungsausgang
- High-Level-Eingabe
- Bassverstärkung (0-6-12dB • 45Hz)
- Variable Eingangsempfindlichkeit
- Überlast- und Wärmeschutz
- Abmessungen: 240(B) x 220(T) x 46(H) mm



- Maximaal vermogen bij 14,4V:
2x 125W/4Ω
of **1x 400W/4Ω** (gebrugd)
- RMS-uitgang bij 14,4V:
2x 50W/4Ω
of **1x 160W/4Ω** (gebrugd)
- RCA-lijningang
- RCA-lijnitgang
- Input op hoog niveau
- Bass Boost (0-6-12dB • 45Hz)
- Variabele ingangsgevoeligheid
- Overbelasting en thermische beveiliging
- Afmetingen: 240(B) x 220(D) x 46(H) mm

Dimensions:

