



CA 1250R4



- Max power output @ 14.4V:
4x 200W/4Ω or 2x 625W/4Ω (bridged)
- RMS output @ 14.4V:
4x 80W/4Ω or 2x 250W/4Ω (bridged)
- Input sensitivity 0,25 - 6V
- RCA line or Aux-in 3,5mm input
- Input level control
- High-/lowpass filter (50-250Hz)
- Bass Boost (0-18dB)
- Thermal protection and short circuit protection
- Dimensions: 215(W) x 35(H) x 103(L)mm



- Puissance max @ 14.4V:
4x 200W/4Ω ou 2x 625W/4Ω (ponté)
- Puissance RMS @ 14.4V:
4x 80W/4Ω ou 2x 250W/4Ω (ponté)
- Sensibilité d'entrée 0,25 - 6V
- Entrée RCA ou par câble auxiliaire jack 3.5 mm
- Niveau d'entrée réglable
- Filtre pass-haut pass-bas (50-250Hz)
- Bass Boost (0-18dB)
- Protection thermique et des courts-circuits
- Dimensions: 215(l) x 35(H) x 103(P) mm

Dimensions:



CALIBER EUROPE BV

Kortakker 10 • 4264 AE Veen
The Netherlands • Tel: +31 416-699 000



www.caliber.nl