

180° ROTATABLE AC OUTLET  
WITH 3 USB PORTS



180° rotatable



## HPS 1101U




- 1 AC outlet type F
- Socket rated max. 250V, 16A total (3680 Watt)
- Fireproof shell
- Child protection
- 180° rotatable
- 3x USB charge output:  
Each USB output : 5.0V DC 2.4A Max  
Total USB output : 5.0V DC 4A Max
- USB Protection:  
Over-Charging protection  
Over-Current protection  
Over-Voltage protection
- LED indicator
- Dimensions: 125(W) x 54(D) x 33(H) mm



- 1 prise secteur type F
- Prise puissance nominale max. 250V, 16A (3680 watts)
- Coque ignifugée
- Sécurité enfant
- 180° rotatif
- 3 sorties de charge USB:  
Chaque sortie USB: 5.0V DC 2.4A Max  
Sortie USB totale: 5.0V DC 4A Max
- Protection USB:  
Protection de sur-charge  
Protection contre les surintensités  
Protection de survoltage
- Indicateur LED
- Dimensions: 125(l) x 54 (P) x 33 (H) mm



3 USB outputs,  
5V max. 2.4A each  
Total 5V DC 4A max.



Child protection

180° ROTATABLE AC OUTLET  
WITH 3 USB PORTS



180° rotatable



## HPS 1101U




- 1 Wechselstrom-Steckdose Typ F
- Schaft bewertet max. 250V, 16A gesamt (3680 Watt)
- Feuerfeste Hülle
- Kinderschutz
- 180° drehbar
- 3x USB-Ladeausgang:  
Jeder USB-Ausgang : 5.0V DC 2.4A Max  
USB-Gesamtausgang: 5,0V DC 4A Max
- USB-Schutz:  
Überladungsschutz  
Überstromschutz  
Überspannungsschutz
- LED-Anzeige
- Abmessungen: 125(B) x 54(T) x 33(H) mm



- 1 AC-uitgang type F
- Socket beoordeeld max. 250V, 16A totaal (3680 Watt)
- Vuurvast omhulsel
- Kinderbescherming
- 180° draaibaar
- 3x USB-opslaguitgang:  
Elke USB-uitgang: 5.0V DC 2.4A Max.  
Totale USB-uitgang: 5.0V DC 4A Max.
- USB-bescherming:  
Overlaadbeveiliging  
Overstroombeveiliging  
Overspanningsbeveiliging
- LED-indicator
- Afmetingen: 125(B) x 54(D) x 33(H) mm



3 USB outputs,  
5V max. 2.4A each  
Total 5V DC 4A max.



Child protection