



IPx6
Water Resistant

Compatible with
Caliber marine units:
• MRM 640BT
• MRM 641BT

MRC 300



- Buttons for: previous/next track, volume up/down, mute, band and mode (to be connected optionally)
- 5m. extension cable
- Partially submerged mounting (installation parts included)
- Dimensions:
Ø61 mm x 46 mm (Ø2.4" x 1.8")
Mounting depth: 29.6 mm (1.2")
Cut out diameter: 51 mm (2")

Marinized:

- Water resistant (IPx6)
- UV resistant (ASTM D4329-057.2.2)
- Salt resistant (ASTM B117-2011)

Compatible with Caliber marine units:

MRM 640BT
MRM 641BT



- Touches: précédent/suivant, augmenter/diminuer le volume, silencieux, bande et mode
- Connexion SWI filaire via un Jack de 3,5 mm
- Touches illuminées (à connecter facultativement)
- Câble d'extension 5 m
- Montage en partie intégré (pièces pour l'installation fournies)
- Dimensions :
Ø61 mm x 46 mm (Ø2,4 po x 1,8 po)
Profondeur du montage : 29,6 mm (1,2 po)
Diamètre de montage : 51 mm (2 po)

Marine:

- Étanche (IPx6)
- Résiste aux UV (ASTM D4329-057.2.2)
- Résiste au sel (ASTM B117-2011)

Compatible avec les produits Caliber Marine :

• MRM 640BT
• MRM 641BT



8 714505 044156



Partially submerged mounting



Illuminated buttons (optional)

